

# STEPHEN FINKEL PHOTOGRAPHY

## Canon Sureshot 130U

The Ultra compact Sure Shot 130u is a fully automatic 35mm lens shutter AF camera. Main features are advanced Light Guide Zoom Flash with Red-Eye Reduction, High-magnification 38-130mm 3.4x zoom lens, Compact, high-quality aluminium design, 16-zone metering sensor for precise exposure control, Integrated focusing and metering linked to the zoom lens and 5 custom functions.

Image Size: 24 x36mm

The Sureshot has a Canon zoom lens 38-130mm f/5.6-12.5 with a real-image zoom viewfinder (approx. 84% coverage) Dioptic Adjustment of -2.5 to +0.5dpt.

Viewfinder information: Picture frame - wide area, AF frame – close-up frame. Table below shows the lamp light meanings.

	Green lamp	Orange Lamp
Lit	Camera ready to shoot (subject in focus)	Flash Ready
Blinking	Too-close warning: 4 times per second Focus warning: 16 times per second	Camera shake warning

Focusing: Passive 3-point AIAF\* Shooting Distance: 0.6m (2.0ft) – infinity Exposure Control Range: Wide angle: 1/560 sec. f/30 – 2 sec. f/5.6. Telephoto: 1/340 sec. f/39 – 2 sec. f/12.5 Film Speeds: DX-coded ISO 25-3000 set automatically in full-stop increments Exposure compensation: Automatic: in backlit conditions, Manual: +1.5 or -1.5 stops Shutter: Electromagnetically controlled programmed shutter/aperture Self-timer: Shoot after 10 sec. Delay

The Flash is a Built-in zoom flash (Recycling time approx. 6 seconds) with 5 Mode:

1. Auto: fires automatically in low light and backlit conditions
2. Flash Auto: with red-eye reduction: Fires automatically in low light and backlit conditions.
3. Flash On: Fires for all shots
4. Flash off: never fires
5. Night Portrait(slow sync) with red-eye reduction: Fire's for all shots

Table shows the Flash distance range:

ISO	Wide-angle	Telephoto
100	0.6 to 3.1m (2.0 to 1.2ft)	0.6 to 2.0 m (2.0 to 6.6 ft)
400	0.6 to 6.2m (2.0 to 20.4 ft)	0.6 to 4.0m (2.0 to 13.2 ft)

There is 5 Custom Functions: real-time release, flash mode memory, disabling automatic film rewind, center-point AF, and continuous shooting. AIAF (Dual AF) Function: AIAF (Artificial Intelligence Auto-focus) has a wide focusing area and is a function for accurate focusing.

Camera Power Source is one CR2 Lithium Battery with a Battery life approx. 17 rolls (24-ex. Normal temperature with 50% flash use) Dimensions of camera (W X H X D): 105 x 58.5 x 45.8mm or 4.1 x 2.3x 1.8 inches. Sureshot can be Remote controlled.

